	uptuo	online.com	aktuonline.com			upt	uonline.co	m	aktuo	nline.c	com	
	Printed Pages: 3 194 NCE-503			uptuonline.	(h)	What are t	he causes	of temporary hardness?				
	(Following Paper ID and Roll No. to be filled in your Answer Book) Paper ID: 100503 Roll No. B.Tech.				(i)	What percentage of total water demand contribut to losses in pipes?				ontributes	s	
					(j)	How muc water?	h DO and	BOD is de	is desired in drinking			
uptuonline.com	(SEM. V) THEORY EXAMINATION, 2015-16					Section-B						_
	ENVIRONMENTAL ENGINEERING-I				ıptu	Attempt any five Parts: (10					10×5-50)	oply lonline.com
	[Time:3 hours] [MaximumMarks:100		onl		Q.2 Explain various types of joints used in water su					er sunniv		
	[Time:3 hours] [MaximumMarks:100 Section-A				ine	system.					v. ouppij	
	O.1 Attem	Attempt all the parts. $(10\times2=20)$.com	com	Q.3 Explain effects of air pollution in detail.						
n aktuonline.com				=		Q.4 Differentiate between design of sewer pipes and water supply pipes. A city has a population of 1,00,000 with a						
	(b) Which source or water contains maximum amount of turbidity?			ak	water supply rate of 200 lpcd. Assuming 75% of water							
			ak		reaches the sewer, what will be the DWF in (m ³ /s)?							
		 (c) Which type of pump is, commonly used hand pump? (d) What is the function of scour valve? (e) What is permissible limit of nitrates in drinking water? (f) Sewers are generally laid, starting from their point. 		aktuonli	aktuonline.com	Q.5 Write a short note on various plumbing fittings used in buildings and houses.						
	(d) V			nline.		Q.6 The population of 5 decades from 1930 to 1976					1970 are	aktuonline.
				com		given. Find out the population after one, two and three decades beyond the last known decade by using						e.com
						arithmetic mean method. Year 1930 1940 1950 1960 1970						
		(g) Pumps are connected to be in to double the discharge and keep the head same.				Populati	on 25,000	28,000	34,000 4	12,000	47,000	
	uptue	online.com (1)	NCE-503 aktuonline.com			upt	uonline.co	(2) om	aktuo	online.c	P.T.O com	

Q.7 What is self-cleanising velocity? What would be the design discharge of a 20 cm diameter sewer being laid at a slope of 0.004 and designed to carry discharge at a depth of 10 cm with Manings n=0.014.

aktuonline.com

uptuonline.com

- Q.8 A combined sewer of circular section is to be designed for a city of population 1,00,000 and an area of 100 ha. The mean flow of the sewage from the city is 250 lpcd. The critical rainfall intensity is 4 cm/hr. Take Manings coefficient as 0.012. Determine the gradient of the sewer from Manings equation to carry a peak flow with a velocity of 1.2 m/s. Take k-0.48.
- Q.9 What aer the types of sewerage system? Explain.

Section-C

Attempt any two parts: (2×15=30)

Q.10 What is plume? Explain various plume behavior in detail

- with the help of neat sketches.
- Q.11 Discuss various population forecasting methods in detail.
- Q.12 Write short note on various methods used for analysis of complex pipe networks. Explain the Hardy Cross method in detail.

(3)